

# SANIMO



## Specifications SANYMO Water Heaters

| <b>EN</b>                           | <b>XB-3</b>                    | <b>XB-3 Combi</b> | <b>XB-6</b>    | <b>XB-6 Combi</b> | <b>XB-10</b>   | <b>XB-10 Combi</b> |
|-------------------------------------|--------------------------------|-------------------|----------------|-------------------|----------------|--------------------|
| Water Capacity                      | 3 liter                        | 3 liter           | 6 liter        | 6 liter           | 10 liter       | 10 liter           |
| Tank Material                       | Stainless Steel                |                   |                |                   |                |                    |
| Housing                             | EPP with High Insulation Value |                   |                |                   |                |                    |
| Temp. Limit                         | 70°C                           |                   |                |                   |                |                    |
| Overheating Protection              | 75°C                           |                   |                |                   |                |                    |
| Insulation Value                    | 0,625 W/mk                     |                   |                |                   |                |                    |
| Heating Element                     | 1                              | 2                 | 1              | 2                 | 1              | 2                  |
| Input Voltage                       | 230 V                          | 230/12 V          | 230 VAC        | 230/12 V          | 230 VAC        | 230/12 V           |
| Power Consumption                   | 300 W                          | 300/200 W         | 300 W          | 300/200 W         | 600 W          | 600/200 W          |
| Power Consumption Stand-by/24 Hours | 0,29 kWh                       | 0,29 kWh          | 0,40 kWh       | 0,40 kWh          | 0,52 kWh       | 0,52 kWh           |
| Heating Time 15-70°C                | 38 min.                        | 38/57 min.        | 76 min.        | 76/115 min.       | 63 min.        | 63/192 min.        |
| Empty Weight                        | 1,3 kg                         | 1,5 kg            | 1,5 kg         | 1,8 kg            | 2,2 kg         | 2,5 kg             |
| Dimensions                          | 250x190x190 mm                 |                   | 300x223x223 mm |                   | 319x270x270 mm |                    |
| Pump Pressure (max.)                | 3,5 bar                        |                   |                |                   |                |                    |
| System Pressure (max.)              | 4,5 bar                        |                   |                |                   |                |                    |
| Suitable for Water Hose             | Ø10 mm                         |                   |                |                   |                |                    |
| EU Drinking Water Standard          | 981831EG                       |                   |                |                   |                |                    |

## Technische Daten SANYMO-Kessel

| DE                                 | XB-3                         | XB-3 Combi | XB-6           | XB-6 Combi  | XB-10          | XB-10 Combi |
|------------------------------------|------------------------------|------------|----------------|-------------|----------------|-------------|
| Wasserkapazität                    | 3 Liter                      | 3 Liter    | 6 Liter        | 6 Liter     | 10 Liter       | 10 Liter    |
| Material des Tanks                 | Edelstahl                    |            |                |             |                |             |
| Gehäuse                            | EPP mit hoher Isolationswert |            |                |             |                |             |
| Temp. Grenze                       | 70°C                         |            |                |             |                |             |
| Überhitzungsschutz                 | 75°C                         |            |                |             |                |             |
| Isolierwert                        | 0,625 W/mk                   |            |                |             |                |             |
| Heizelement                        | 1                            | 2          | 1              | 2           | 1              | 2           |
| Eingangsspannung                   | 230 V                        | 230/12 V   | 230 VAC        | 230/12 V    | 230 VAC        | 230/12 V    |
| Stromverbrauch                     | 300 W                        | 300/200 W  | 300 W          | 300/200 W   | 600 W          | 600/200 W   |
| Stromverbrauch Stand-by/24 Stunden | 0,29 kWh                     | 0,29 kWh   | 0,40 kWh       | 0,40 kWh    | 0,52 kWh       | 0,52 kWh    |
| Aufwärmzeit 15-70°C                | 38 min.                      | 38/57 min. | 76 min.        | 76/115 min. | 63 min.        | 63/192 min. |
| Leergewicht                        | 1,3 kg                       | 1,5 kg     | 1,5 kg         | 1,8 kg      | 2,2 kg         | 2,5 kg      |
| Abmessungen                        | 250x190x190 mm               |            | 300x223x223 mm |             | 319x270x270 mm |             |
| Pumpendruck (max.)                 | 3,5 bar                      |            |                |             |                |             |
| Systemdruck (max.)                 | 4,5 bar                      |            |                |             |                |             |
| Geeignet für Wasserschlauch        | Ø10 mm                       |            |                |             |                |             |
| EU Trinkwassernorm                 | 981831EG                     |            |                |             |                |             |

## Specificaties SANYMO Boilers

**NL**

| NL                             | XB-3                        | XB-3 Combi | XB-6           | XB-6 Combi  | XB-10          | XB-10 Combi |
|--------------------------------|-----------------------------|------------|----------------|-------------|----------------|-------------|
| Waterinhoud                    | 3 liter                     | 3 liter    | 6 liter        | 6 liter     | 10 liter       | 10 liter    |
| Materiaal tank                 | Roestvrijstaal              |            |                |             |                |             |
| Behuizing                      | EPP met hoge isolatiewaarde |            |                |             |                |             |
| Temp. limiet                   | 70°C                        |            |                |             |                |             |
| Oververhittingsbeveiliging     | 75°C                        |            |                |             |                |             |
| Isolatiewaarde                 | 0,625 W/mk                  |            |                |             |                |             |
| Verwarmingselement             | 1                           | 2          | 1              | 2           | 1              | 2           |
| Ingangsspanning                | 230 V                       | 230/12 V   | 230 VAC        | 230/12 V    | 230 VAC        | 230/12 V    |
| Stroomverbruik                 | 300 W                       | 300/200 W  | 300 W          | 300/200 W   | 600 W          | 600/200 W   |
| Stroomverbruik stand-by/24 uur | 0,29 kWh                    | 0,29 kWh   | 0,40 kWh       | 0,40 kWh    | 0,52 kWh       | 0,52 kWh    |
| Opwarmtijd 15-70°C             | 38 min.                     | 38/57 min. | 76 min.        | 76/115 min. | 63 min.        | 63/192 min. |
| Gewicht leeg                   | 1,3 kg                      | 1,5 kg     | 1,5 kg         | 1,8 kg      | 2,2 kg         | 2,5 kg      |
| Afmetingen                     | 250x190x190 mm              |            | 300x223x223 mm |             | 319x270x270 mm |             |
| Pompdruk (max.)                | 3,5 bar                     |            |                |             |                |             |
| Systeemdruk (max.)             | 4,5 bar                     |            |                |             |                |             |
| Geschikt voor waterslang       | Ø10 mm                      |            |                |             |                |             |
| EU drinkwaternorm              | 981831EG                    |            |                |             |                |             |